



# **MOVING SHM INTO ROUTINE USE – PROGRESS IN CVM APPLICATIONS**

**A4A NDT Forum September 16 – 19, 2019**

John R. Linn, Senior Engineer  
Structural Monitoring Systems

Dr. Dennis Roach, Senior Technical Fellow  
Sandia National Laboratories

# Contents

- ① Overview of physics of crack detection using CVM.
- ③ Applications and status.
- ④ New regulatory documents.
- ⑤ Conclusions.

**STRUCTURAL**  
MONITORING  
SYSTEMS  
plc



# An In-Situ Crack Detection Solution

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc




- A quarter century of R&D.
- Developed for use in aerospace environments.
- Fully integrated for in-situ aircraft crack detection.
- Reduces inspection time for structural inspections.
- Increases aircraft utilization.
- Reduces false positive indications.
- Reduces access time and damage during access
- Reduces aircraft down time.
- Does not need to be performed in a hanger environment.
- Fail safe and built in self test technology when we measure for continuity.





# TECHNOLOGY OVERVIEW

# Technology Overview

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc




- ✓ A sensor has alternating Vacuum (red) galleries and Ambient (blue) pressure galleries.
- ✓ Galleries are adhered to the part surface.
- ✓ The structure surface becomes an integral part of the sensor system.



# TECHNOLOGY – HOW IT WORKS

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc



A Flow Meter measures the differential across the sensor vacuum gallery and the vacuum source and compares them for any change.



A steady state vacuum is maintained with no pressure differential being read across the Flow Meter.



Should a crack occur, a leakage path (breach) between the vacuum and ambient galleries will result.



As the crack propagates, the bridge across the vacuum & ambient galleries increases causing further loss of vacuum.



The Flow Meter will display this as an increase in pressure differential as both galleries mix.

# TECHNOLOGY – SENSOR INSTALLATION

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc



- ✓ Test fit sensor.
- ✓ Clean surrounding area.
- ✓ Sand surface smooth.
- ✓ Clean surrounding area again with DI H<sub>2</sub>O.
- ✓ Apply sensor and consolidate to surface.
- ✓ Connect tubing to Sensor Lead Socket.
- ✓ Test with PM200.
- ✓ Fail safe and self test technology when measure continuity

## Additional CVM Information

- Detects surface cracks.
- Sensors are translucent so cracks can be visually detected.
- Currently used on metallic parts with or without primer. Smaller crack size detected when primer is applied on the parts.
- Sensors have flown on airplanes for 15+ years and still functional.
- Sensors remain onboard during flights.
- Instrument does not remain onboard.
- Customized installation and NDT procedure required for each application.
- Procedures have Frequently Asked Questions (FAQ) and Fault Isolation process.
- Sensors are made from Teflon and are passive, with no EMI or EMC concerns.
- If required, the sensors can be removed to perform other NDT inspections.

**STRUCTURAL**  
MONITORING  
SYSTEMS  
plc





# Detailed CVM Procedure

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc



- **Very similar to traditional NDT Procedures**
- Detailed part access as required
- Sensor details and required instrument details
- Necessary materials list
  - Sandpaper grit and type/ DI water/primer/paint/overcoat/rags/scrapers types/solvents/gloves/masks/...
- Inspection locations
  - Distance and tolerance fastener heads/tails...
  - Installation Dwg, showing routing details
  - Lead tie details
- Sensor installation
  - Remove scrape sealant/Fuel Vapor Barrier, sand surface/inspect for paint/primer condition
  - Bulk cleaning steps
  - Detailed Cleaning steps
  - Paint and/or prime requirements
- System tests / calibration
- Inspection process/details
- Fault Isolation Section
  - Flow chart and FAQ

# Detailed CVM Procedure (Continued)

Procedure contents

**STRUCTURAL  
MONITORING  
SYSTEMS**



- a. → Connect the Verification Block to the Instrument Lead.
- b. → Turn on the PM200. Follow on screen prompts.
- c. → Select operator.



PM200-Operator-Selection-Screen

- d. → If the Instrument Lead is not connected, the PM200 will prompt for its connection.



PM200-Connect-Instrument-Lead-Screen

- e. → If the Sensor Lead Socket is not connected, the PM200 will prompt for its connection.



- f. → Press Start to Begin Test.




PM200-Press-Start-to-Begin-Test

- g. → After completion of a successful test the PM200 should report ALL TESTS PASSED. If any other screens other than the above sequence occur, refer to the PM200 Operator's Manual.





# CVM™ APPLICATIONS

# 737 Center Wing Box Front Spar Shear Fitting Service Bulletin 737 57-1309



SB revised to include CVM as an inspection option.




FRONT SPAR AND WING CEN

# 737 NDT Manual - New SHM Chapter Published (Nov 2015)

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc





**MyBoeingFleet**  
Maintenance Documents

Maintenance Docs      Contact Us      Help

Maintenance & Repair Documents      Select a Product or Service... ▼


### 737 Non-Destructive Testing Manual

Document: D6-37239  
Revision: 15Nov2015  
Rev Level: 117

Search this document for:  [Submit](#) [Supplemental Videos](#)  
[Search Tips](#) [Go Back](#)

#### Non-Destructive Testing Manual

Check boxes to add or remove from search. [Check All](#) | [Uncheck All](#)

- [FRONT MATTER](#)
- [PART 01 - GENERAL](#)
- [PART 02 - X-RAY](#)
- [PART 04 - ULTRASONIC](#)
- [PART 05 - STRUCTURAL HEALTH MONITORING](#) 
- [PART 06 - EDDY CURRENT](#)
- [PART 09 - THERMOGRAPHY](#)
- [PART 10 - VISUAL/OPTICAL](#)


Shear Fitting CVM Procedure  
Part 5, 57-10-01

# Boeing Service Bulletin – Revised to Allow for Routine Use of SHM Solution (June 2016)

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc



## BOEING SERVICE BULLETIN 737-57-1309



**DO A DETAILED INSPECTION OR COMPARATIVE VACUUM MONITORING (CVM) INSPECTION OF**

THE CENTER WING BOX FRONT SPAR SHEAR FITTINGS FOR ANY CRACKS. IF ANY CRACK IS FOUND, REMOVE THE DAMAGED SHEAR FITTING, MAKE SURE THERE IS NO CRACKING IN THE UPPER PANEL AND INSTALL A NEW SHEAR FITTING AS GIVEN IN THIS SERVICE BULLETIN.

AT EACH SHEAR FITTING, IF NO CRACKING IS FOUND IT IS OPTIONAL TO ACCOMPLISH THE PREVENTIVE MODIFICATION BY REPLACING THE SHEAR FITTINGS.



Commercial  
Airplanes

**737**

Service Bulletin

**Number:** 737-57-1309  
**Original Issue:** January 28, 2011  
**Revision 1:** June 27, 2016  
**ATA System:** 5714

**Revision Transmittal Sheet**

**SUBJECT:** WINGS - Center Wing Box - Front Spar Shear Fitting - Inspection, Repair and Preventive Modification

This revision includes all pages of the service bulletin.

### COMPLIANCE INFORMATION RELATED TO THIS REVISION

Effects of this Revision on airplanes on which Original Issue was previously done:



None.

### REASON FOR REVISION

This revision is sent to add a Comparative Vacuum Monitoring (CVM) inspection as an alternative inspection method for the front spar shear fitting. In addition, illustrations in figures are changed to show correct views, footnotes are added in fastener tables for clarification and footnotes in figures are changed to clarify sealing instructions.

# Boeing Service Bulletin – 737 53A1248 Aft Pressure Bulkhead Inspection



STRUCTURAL  
MONITORING  
SYSTEMS  
plc



- 1,200 FC repeat threshold for LFEC and detailed inspections **Aft side** S-5L to S-7L and S-5R to S-9R.
- CVM sensors installed on the **Fwd side** of the APB.
- Approximately 21-23 sensors chains per airplane
- **Access time and Inspection ~ 1hr 15 min**
- **Airline reported 12 Hrs typical**
- Reduced airplane downtime, reduced false calls, reduced inspection times

# 737 Aft Pressure Bulkhead

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc



**20 aircraft  
installations in  
2019**

**Circumferential cracks at fasteners connecting the web assembly to the bulkhead "Y" chord.**





# WiFi Antenna Installation Structure (multiple aircraft types, multiple airlines)




**CVM sensors used to rapidly complete frequent, repeat HFEC/LFEC inspections required on internal structure hidden behind interior panels.  
Anticipate Installations in 1<sup>th</sup> Q 2020**

**STRUCTURAL  
MONITORING  
SYSTEMS**  
INC




**CVM Sensor  
Horseshoe  
Design and  
Ring Sensors  
Many other  
Designs**



**2 Ring and 3 Sensor  
ganged together**

# CVM Applications on Rotorcraft


## CVM Intercept Sensors




## CVM Ring Sensor

### CVM Ring Sensor

- Will detect cracks after they extend out from under the fastener - sensitivity will exceed visual detection capabilities and match eddy current inspections
- May be the only sensor needed (on each side) if cracks originate here



- Cracks originate at bolt hole (bore) with propagation in multiple directions
- Inspection requirement – visual (1" – 2" L crack)



### CVM Intercept Sensors

- Monitors for cracks that may originate from upper row of fasteners
- Fits between the fasteners and mounts around the radius corner



# MANUFACTURING AND ENGINEERING

# AEM CERTIFICATION AND STANDARDS



**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc



- ✔ Transport Canada Approved Manufacturer and Maintenance Organisation, pending Design Approval Organisation (DAO)  
Certification Manager – Trevor Lynch-Staunton
- ✔ EASA Part 145 European Maintenance Approval
- ✔ ISO9001/AS9100C registered
- ✔ Registered, Canadian Controlled Goods Program (CGP)  
- Eligible for ITAR Exemptions
- ✔ Illuminated front panel design and manufacturing per SAE AS7788, DO-275 and MIL STD-3009



# Regulators New Documents

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc




- **FAA AC 43-218 Draft Released by Flight Standards Service Division**
  - Provides guidance to develop an operator's Integrated Aircraft Health Management (IAHM) program.
  - Encompasses aircraft systems, data transmission, and data analysis/implementation.
    - Describes Design Approval Holder (DAH) responsibilities.
    - Outlines trigger requirement for maintenance action.
    - Provides training, data transmission performance, and data security requirements.
    - Not to be used as a substitute for the performance of a Required Inspection Item (RII).
    - Requires operator procedures and notification to regulatory oversight office of intent.
- **FAA Transport Standards Branch** Currently Working on Issue Paper (IP) to establish the minimum requirements of a specific CVM application. This IP will be used develop the general requirements of a **generic IP** for other SHM applications to satisfy regulator inspection compliance.
  - Required testing for structural, environmental, materials, coatings, durability, and systems tests.
  - Probability of Detection (POD) methods and requirement's.
  - Impact of SHM on-board equipment with the ability to perform other NDT inspections.
  - Proven reliability and high confidence of performance.

# Conclusions

**STRUCTURAL  
MONITORING  
SYSTEMS**  
plc



- Cost savings technology
- Many different applications in aviation and other applications
- Transitioning from research to routine applications
- FAA provided SHM requirement documents



**STRUCTURAL  
MONITORING  
SYSTEMS  
plc**

**USA**

---

**Toby Chandler**  
Chief Executive Officer

**Michael Reveley**  
Executive Director

1999 Avenue Of the Stars Suite 1100  
Century City, CA 90067  
United States | Tel: +1 310 292 5474

**AUSTRALIA**

---

**Sam Wright**  
Company Secretary

**Andrew Chilcott**  
Non-Executive Director

Suite 39, 1 Freshwater Parade  
Claremont WA 6010  
Australia | Tel: +61 8 6364 0899

**NEW ZEALAND**

---

**Will Rouse**  
Executive Director

91 St. Stephens Ave,  
Parnell, Auckland  
Tel: +64 21 743 618